

## ATTENTION

- Tyre pressure is the most important factor for tyre performance and good tyre maintenance.
- The recommended tyre pressures are for vehicles working in standard conditions and loading at nominal weight.
- It is recommended to contact your Goodyear OTR representative in order to adapt the pressures to your specific material and working conditions.

For any specific application, please contact your local Goodyear sales representative.

# GOODYEAR<sup>®</sup> OFF-THE-ROAD

## PRESSURE RECOMMENDATIONS FOR BELL.

### GET THE MOST OUT OF YOUR GOODYEAR OTR TYRES

Maximise your Bell and Goodyear OTR tyres potential by using the correct pressure.



### Trusted Products

Specialized OTR Innovations  
to Help Lower Operating Costs



### Worldwide Support

Global Support Network to Help  
Keep Your Fleet Running Efficiently



### Reliable Services

Expert Field Support to Help  
You Optimise Operations



### Management Tools

Value-Added Tools to Help Grow  
Your Business with Confidence

Consult your Goodyear representative for additional information.  
Produced by Goodyear Dunlop Tyres Operations S.A. 293/0715/LUX-ENG

[www.goodyearotr.com](http://www.goodyearotr.com)

©2017 The Goodyear Tire & Rubber Company. All rights reserved.

**GOODYEAR**  
OFF-THE-ROAD





**BELL**

**GOODYEAR**  
OFF-THE-ROAD

# PRESSURE RECOMMENDATIONS FOR BELL

## Tyres for Bell Articulated Dump Trucks



	<b>GP-3D</b> 115 (L3)	<b>TL-3A+</b> 125 (E3+)	<b>GP-4D</b> 150 (L4)	<b>RT-4A / RT-4A+</b> 170 (E4+)	<b>RM-4A / RM-4B+</b> 170 (E4+)
					
<b>TYRE RATING</b>	Mixed Application, Traction, Comfort, Stability, 65 series only	Exceptional Traction, Comfort, Soil & Clay, Sidewall Protection	Transport, Traction, Flotation, Long tread life	Transport, Traction, Improved hard surface, Long tread life	Aggressive extra deep tread pattern offers improved tread wear, forward & lateral traction
Abrasion and Cut Resistance	6	6	7	8	9
Heat Resistance	8	9	8	8	8
Traction	7	10	8	8	6
Stability	8	8	8	8	8
Self Cleaning	7	9	7	8	7
Longevity	6	8	8	9	8
Comfort	8	9	8	8	9

### INFLATION RECOMMENDATION\*\*\* (bar / psi)

MODELS	DIMENSION	FRONT	MIDDLE	REAR
B20E	18t 20.5 R 25	2.75 / 40	4.00 / 58	4.00 / 58
	19.8t 20.5 R 25	2.75 / 40	4.25 / 62	4.25 / 62
B25E	23.5 R 25	2.75 / 40	4.25 / 62	4.25 / 62
	750/65 R 25	2.25 / 33	3.25 / 47	3.25 / 47
B25E	6x4 Supertruck 20.5 R 25	3.75 / 54	5.00 / 73	5.00 / 73
B30E	23.5 R 25	3.25 / 47	5.00 / 73	5.00 / 73
	750/65 R 25	2.50 / 36	4.00 / 58	4.00 / 58
B35E	26.5 R 25	4.25 / 62	4.75 / 69	4.75 / 69
B40D	29.5 R 25	3.50 / 51	4.25 / 62	4.25 / 62
B40E	29.5 R 25	3.50 / 51	4.25 / 62	4.25 / 62
	875/65 R 29	3.00 / 44	3.50 / 51	3.50 / 51
B45D	29.5 R 25	3.50 / 51	4.25 / 62	4.25 / 62
B45E	29.5 R 25	3.50 / 51	4.25 / 62	4.25 / 62
	875/65 R 29	3.00 / 44	3.75 / 54	3.75 / 54
B50E	29.5 R 25	4.00 / 58	5.00 / 73	5.00 / 73
	875/65 R 29	3.50 / 51	4.25 / 62	4.25 / 62
B60E	875/65 R 29	3.75 / 54		
B60E	24.00 R 35			7.25 / 105