
GOODYEAR[®] OFF-THE-ROAD

PRESSURE RECOMMENDATIONS FOR LIEBHERR.

GET THE MOST OUT OF YOUR GOODYEAR OTR TYRES

Maximise your Liebherr and Goodyear OTR tyres potential by using the correct pressure.



LIEBHERR

GOODYEAR
OFF-THE-ROAD

PRESSURE RECOMMENDATIONS FOR LIEBHERR

Tyres for LIEBHERR Wheel Loaders



	RT-3B 115 (L3)	GP-3D 115 (L3)	TL-3A+ 125 (L3+)	RL-2+ 125 (L3+)	GP-4D 150 (L4)	RL-4K 150 (L4)	RL-5K 250 (L5)	RT-5D 250 (L5)
TYRE RATING								
Abrasion and Cut Resistance	7	7	6	6	7	8	9	9
Heat Resistance	8	8	9	9	8	7	5	7
Traction	8	8	10	10	8	4	5	9
Stability	8	8	8	8	8	9	9	9
Self Cleaning	7	7	9	9	7	5	5	8
Longevity	6	6	8	8	8	8	10	9
Comfort	8	7	9	9	8	7	8	8

INFLATION RECOMMENDATION*
(bar / psi)

MODELS	DIMENSION								FRONT	REAR
L 506 John Deer 204L	335/80 R 18								3.00 / 44	2.40 / 35
	365/70 R 18								3.50 / 51	2.75 / 40
	405/70 R 18								3.00 / 44	2.50 / 36
	365/80 R 20								3.00 / 44	2.25 / 33
	405/70 R 20								2.75 / 40	2.25 / 33
L 507 John Deer 224K	365/70 R 18 EM								3.75 / 54	2.50 / 36
	405/70 R 18								3.00 / 44	2.00 / 29
	335/80 R 20 EM								3.50 / 51	2.25 / 33
	365/80 R 20 EM								3.00 / 44	2.25 / 33
L 508 C John Deer 304L	405/70 R 20								2.75 / 40	2.00 / 29
	335/80 R 18								3.20 / 46	2.60 / 38
	405/70 R 18								3.50 / 51	2.50 / 36
	365/80 R 20 EM								3.50 / 51	2.50 / 36
L 509 ST John Deer 304J	405/70 R 20								3.25 / 47	2.25 / 33
	405/70 R 18								3.75 / 54	2.50 / 36
	365/80 R 20 EM								3.75 / 54	2.50 / 36
	405/70 R 20								3.50 / 51	2.50 / 36
L 514 IV	455/70 R 20 EM								2.75 / 40	2.00 / 29
	17.5 - 25								2.50 / 36	2.00 / 29
	17.5 R 25	•		•					3.25 / 47	2.00 / 29
	17.5 - 25								2.75 / 40	2.00 / 29
L 518	17.5 R 25	•		•			•	•	3.50 / 51	2.00 / 29
	17.5 - 25								4.50 / 65	3.00 / 44
	17.5 R 25	•		•			•	•	5.00 / 73	3.50 / 51
	20.5 - 25								2.75 / 40	2.00 / 29
L 526 P-Kin L 526 Z-Kin	20.5 R 25	•		•	for Latin American Market only	•	•	•	3.50 / 51	2.50 / 36
	550/65 R 25		•						4.00 / 58	2.75 / 40
	20.5 - 25								3.00 / 44	2.00 / 29
	20.5 R 25	•		•	for Latin American Market only	•	•	•	3.75 / 54	2.00 / 29
L 538	600/65 R 25		•						3.50 / 51	2.00 / 29
	650/65 R 25		•						3.00 / 44	2.00 / 29
	20.5 - 25								3.75 / 54	2.00 / 29
L 546	20.5 R 25	•		•	for Latin American Market only	•	•	•	3.75 / 54	2.00 / 29
	600/65 R 25		•						3.75 / 54	2.00 / 29
	650/65 R 25		•						3.25 / 47	2.00 / 29

PRESSURE RECOMMENDATIONS FOR LIEBHERR

Tyres for LIEBHERR Wheel Loaders



TYRE RATING

	RT-3B 115 (L3)	GP-3D 115 (L3)	TL-3A+ 125 (L3+)	RL-2+ 125 (L3+)	GP-4D 150 (L4)	RL-4K 150 (L4)	RL-5K 250 (L5)	RT-5D 250 (L5)
Abrasion and Cut Resistance	7	7	6	6	7	8	9	9
Heat Resistance	8	8	9	9	8	7	5	7
Traction	8	8	10	10	8	4	5	9
Stability	8	8	8	8	8	9	9	9
Self Cleaning	7	7	9	9	7	5	5	8
Longevity	6	6	8	8	8	8	10	9
Comfort	8	7	9	9	8	7	8	8

INFLATION RECOMMENDATION*
(bar / psi)

MODELS	DIMENSION	FRONT	REAR
L 550 XPower	23.5 - 25	3.75 / 54	2.25 / 33
	23.5 R 25	4.00 / 58	2.50 / 36
	650/65 R 25	4.25 / 62	2.75 / 40
	750/65 R 25	3.25 / 47	2.00 / 29
L 550 XPower HKS L 550 XPower Holzgreifer	23.5 - 25	4.00 / 58	2.50 / 36
	23.5 R 25	4.50 / 65	3.00 / 44
	650/65 R 25	4.75 / 69	3.25 / 47
	750/65 R 25	3.50 / 51	2.00 / 29
L 556 XPower	23.5 - 25	4.00 / 58	2.50 / 36
	23.5 R 25	4.50 / 65	3.00 / 44
	650/65 R 25	4.75 / 69	3.25 / 47
	750/65 R 25	3.50 / 51	2.00 / 29
L 556 XPower HKS L 556 XPower Holzgreifer	23.5 - 25	4.75 / 69	3.25 / 47
	23.5 R 25	5.00 / 73	3.50 / 51
	750/65 R 25	3.75 / 54	2.25 / 33
	26.5 - 25	3.75 / 54	2.25 / 33
L 566 XPower	26.5 R 25	4.50 / 65	3.00 / 44
	750/65 R 25	4.50 / 65	3.00 / 44
	775/65 R 29	3.50 / 51	2.00 / 29
	26.5 - 25	4.50 / 65	3.00 / 44
L 566 XPower HKS L 566 XPower Holzgreifer	26.5 R 25	4.75 / 69	3.25 / 47
	750/65 R 25	4.75 / 69	3.25 / 47
	775/65 R 29	3.75 / 54	2.25 / 33
	26.5 - 25	4.50 / 65	3.25 / 47
L 576 XPower	26.5 R 25	5.25 / 76	3.75 / 54
	750/65 R 25	5.00 / 73	3.50 / 51
	775/65 R 29	4.25 / 62	2.75 / 40
	26.5 - 25	4.50 / 65	3.25 / 47
L 580 XPower	26.5 R 25	5.25 / 76	3.75 / 54
	750/65 R 25	5.00 / 73	3.50 / 51
	775/65 R 29	4.75 / 69	3.25 / 47
	26.5 R 25	5.25 / 76	3.75 / 54
L 580 XPower HKS L 580 XPower Holzgreifer	775/65 R 29	4.75 / 69	3.25 / 47
	29.5 R 25	5.75 / 83	4.25 / 62
L 586 XPower	875/65 R 29	4.50 / 65	2.75 / 40

PRESSURE RECOMMENDATIONS FOR LIEBHERR

Tyres for LIEBHERR Wheel Loaders



	HRL DL-3A 100 (L3)	HRL DL-5A 250 (L5)	SGL DL-2A 100 (L2)	Dunlop SPT-9 L-2
TYRE RATING				
Abrasion and Cut Resistance	6	8	6	5
Heat Resistance	8	7	9	9
Traction	7	7	8	7
Stability	6	6	5	6
Self Cleaning	8	8	8	8
Longevity	6	7	5	5
Comfort	8	8	8	8

INFLATION RECOMMENDATION*
(bar / psi)

MODELS	DIMENSION	FRONT	REAR
L 506 John Deere 204L	335/80 R 18	3.00 / 44	2.40 / 35
	365/70 R 18	3.50 / 51	2.75 / 40
	405/70 R 18	3.00 / 44	2.50 / 36
	365/80 R 20	3.00 / 44	2.25 / 33
	405/70 R 20	2.75 / 40	2.25 / 33
L 507 John Deere 224K	365/70 R 18 EM	3.75 / 54	2.50 / 36
	405/70 R 18	3.00 / 44	2.00 / 29
	335/80 R 20 EM	3.50 / 51	2.25 / 33
	365/80 R 20 EM	3.00 / 44	2.25 / 33
L 508 C John Deere 304L	405/70 R 20	2.75 / 40	2.00 / 29
	335/80 R 18	3.20 / 46	2.60 / 38
	405/70 R 18	3.50 / 51	2.50 / 36
	365/80 R 20 EM	3.50 / 51	2.50 / 36
L 509 ST John Deere 304J	405/70 R 20	3.25 / 47	2.25 / 33
	405/70 R 18	3.75 / 54	2.50 / 36
	365/80 R 20 EM	3.75 / 54	2.50 / 36
L 514 IV	405/70 R 20	3.50 / 51	2.50 / 36
	455/70 R 20 EM	2.75 / 40	2.00 / 29
	17.5 - 25	2.50 / 36	2.00 / 29
L 518	17.5 R 25	3.25 / 47	2.00 / 29
	17.5 - 25	2.75 / 40	2.00 / 29
L 526 P-Kin L 526 Z-Kin	17.5 R 25	3.50 / 51	2.00 / 29
	20.5 - 25	4.50 / 65	3.00 / 44
	20.5 R 25	5.00 / 73	3.50 / 51
	20.5 - 25	2.75 / 40	2.00 / 29
	550/65 R 25	3.50 / 51	2.50 / 36
L 538	600/65 R 25	4.00 / 58	2.75 / 40
	650/65 R 25	3.00 / 44	2.00 / 29
	20.5 - 25	3.00 / 44	2.00 / 29
	20.5 R 25	3.75 / 54	2.00 / 29
L 546	600/65 R 25	3.50 / 51	2.00 / 29
	650/65 R 25	3.00 / 44	2.00 / 29
	20.5 - 25	3.75 / 54	2.00 / 29

Tyres for LIEBHERR Wheel Loaders



	HRL DL-3A 100 (L3)	HRL DL-5A 250 (L5)	SGL DL-2A 100 (L2)	Dunlop SPT-9 L-2
TYRE RATING				
Abrasion and Cut Resistance	6	8	6	5
Heat Resistance	8	7	9	9
Traction	7	7	8	7
Stability	6	6	5	6
Self Cleaning	8	8	8	8
Longevity	6	7	5	5
Comfort	8	8	8	8

INFLATION RECOMMENDATION*
(bar / psi)

MODELS	DIMENSION	FRONT	REAR
L 550 XPower	23.5 - 25	3.75 / 54	2.25 / 33
	23.5 R 25	4.00 / 58	2.50 / 36
	650/65 R 25	4.25 / 62	2.75 / 40
	750/65 R 25	3.25 / 47	2.00 / 29
	23.5 - 25	4.00 / 58	2.50 / 36
L 550 XPower HKS L 550 XPower Holzgreifer	23.5 R 25	4.50 / 65	3.00 / 44
	650/65 R 25	4.75 / 69	3.25 / 47
	750/65 R 25	3.50 / 51	2.00 / 29
L 556 XPower	23.5 - 25	4.00 / 58	2.50 / 36
	23.5 R 25	4.50 / 65	3.00 / 44
	650/65 R 25	4.75 / 69	3.25 / 47
L 556 XPower HKS L 556 XPower Holzgreifer	750/65 R 25	3.50 / 51	2.00 / 29
	23.5 - 25	4.75 / 69	3.25 / 47
	23.5 R 25	5.00 / 73	3.50 / 51
L 566 XPower	750/65 R 25	3.75 / 54	2.25 / 33
	26.5 - 25	3.75 / 54	2.25 / 33
	26.5 R 25	4.50 / 65	3.00 / 44
	750/65 R 25	4.50 / 65	3.00 / 44
L 566 XPower HKS L 566 XPower Holzgreifer	775/65 R 29	3.50 / 51	2.00 / 29
	26.5 - 25	4.50 / 65	3.00 / 44
	26.5 R 25	4.75 / 69	3.25 / 47
L 576 XPower	750/65 R 25	4.75 / 69	3.25 / 47
	775/65 R 29	4.75 / 69	3.25 / 47
	26.5 - 25	3.75 / 54	2.25 / 33
L 580 XPower	26.5 R 25	4.50 / 65	3.25 / 47
	26.5 - 25	5.25 / 76	3.75 / 54
	750/65 R 25	5.00 / 73	3.50 / 51
	775/65 R 29	4.25 / 62	2.75 / 40
L 580 XPower HKS L 580 XPower Holzgreifer	26.5 R 25	4.50 / 65	3.25 / 47
	775/65 R 29	5.25 / 76	3.75 / 54
L 586 XPower	29.5 R 25	4.75 / 69	3.25 / 47
	875/65 R 29	5.75 / 76	4.25 / 62

ATTENTION

- Tyre pressure is the most important factor for tyre performance and good tyre maintenance.
- The recommended tyre pressures are for vehicles working in standard conditions and loading at nominal weight.
- It is recommended to contact your Goodyear OTR representative in order to adapt the pressures to your specific material and working conditions.

For any specific application, please contact your local Goodyear sales representative.



Trusted Products

Specialized OTR Innovations
to Help Lower Operating Costs



Worldwide Support

Global Support Network to Help
Keep Your Fleet Running Efficiently



Reliable Services

Expert Field Support to Help
You Optimise Operations



Management Tools

Value-Added Tools to Help Grow
Your Business with Confidence

Consult your Goodyear representative for additional information.
Produced by Goodyear Dunlop Tyres Operations S.A. 293/0715/LUX-ENG

www.goodyearotr.com

©2017 The Goodyear Tire & Rubber Company. All rights reserved.

GOODYEAR
OFF-THE-ROAD