

DUNLOP PRESSURE RECOMMENDATIONS



DUNLOP
FOREVER FORWARD

SP PG7 / SP T9

PRESSURE RECOMMENDATIONS FOR VOLVO



Tyres for VOLVO Compact Wheel Loaders

SP PG7
100 (L2)

SP T9
100 (L2)

TYRE RATING

	SP PG7	SP T9
Abrasion and Cut Resistance	5	5
Heat Resistance	9	9
Traction	8	7
Stability	6	6
Self Cleaning	8	8
Longevity	5	5
Comfort	8	8

INFLATION RECOMMENDATION (bar)

MODELS	DIMENSION	INFLATION RECOMMENDATION (bar)	
		FRONT	REAR
L 20F	15.5/55R18 TL MPT 14PR 134E	2.50	2.50
	335/80R18 TL EM 145A2/134B	2.25	2.25
	365/70R18 TL EM 146A2/135B	2.00	2.00
	405/70R18 TL EM 153A2/141B	1.75	1.75
	335/80R20 TL EM 147A2/136B	2.25	2.25
L 25F	15.5/55R18 TL MPT 14PR 134E	3.25	2.50
	335/80R18 TL EM 145A2/134B	3.00	2.50
	365/70R18 TL EM 146A2/135B	2.75	2.25
	405/70R18 TL EM 153A2/141B	2.50	2.00
	335/80R20 TL EM 147A2/136B	2.75	2.50
L 28F	365/70R18 TL EM 146A2/135B	2.75	2.25
	405/70R18 TL EM 153A2/141B	2.75	2.25
	335/80R20 TL EM 147A2/136B	2.75	2.25
L 30G	15.5/55R18 TL MPT 14PR 134E	4.00	3.00
	365/70R18 TL EM 146A2/135B	3.50	2.75
	405/70R18 TL EM 153A2/141B	3.00	2.25
	335/80R20 TL EM 147A2/136B	3.25	2.75
	365/80R20 TL EM 153A2/141B	3.00	2.50
	405/70R20 TL EM 155A2/143B	2.75	2.25
	455/70R20 TL EM 162A2/154B	2.50	2.00
L 35G	15.5/55R18 TL MPT 14PR 134E	4.50	3.50
	405/70R18 TL EM 153A2/141B	3.50	2.75
	335/80R20 TL EM 147A2/136B	3.75	3.50
	365/80R20 TL EM 153A2/141B	3.50	2.75
	405/70R20 TL EM 155A2/143B	3.00	2.50
	455/70R20 TL EM 162A2/154B	2.50	2.00
L 45G	455/70R24 TL EM 165A2/154B	3.40	2.25
L 50G	455/70R24 TL EM 165A2/154B	3.75	2.60

ATTENTION

- Tyre pressure is the most important factor for tyre performance and good tyre maintenance.
- The recommended tyre pressures are for vehicles working in standard conditions and loading at nominal weight.
- It is recommended to contact your Dunlop OTR representative in order to adapt the pressures to your specific material and working conditions.

For additional information, please contact your local Dunlop sales representative.

otr.dunlop.eu